

ArroChem[®] INCORPORATED

SPECIALTY AND INDUSTRIAL CHEMICALS

P.O. Box 5, 201 Westland Farm Road, Mt. Holly, NC 28120

TEL: 704-827-0216 FAX: 704-822-1150

email: contactus@arrochem.com

ARROBRITE PRESOAK

General Characteristics:

| | |
|-----------------------|--------------------------------|
| Appearance: | Colorless Clear Liquid |
| Chemical Composition: | Oxygenated Hydrocarbon Solvent |
| Viscosity: | 10 - 30 cps (25°C, 1 atm) |
| Solubility in Water: | Good |
| pH, 1% Solution: | 7 |
| Foaming Nature: | Non-Foaming |

Application: *

ArroBrite Presoak can be sprayed, wiped, or brushed onto surface for removal of grease and foreign matter from steel, aluminum, cast iron or other substrates. ArroBrite Presoak contains no water and can be used over a wide range of temperatures. For removal and rinsing, a second application of ArroBrite Presoak used to flush surface free of soils, followed by air-drying, is sufficient for effective cleaning.



*As conditions vary, all dosages and guidelines are merely suggested starting points; it is recommended the user determine the proper operating conditions for his/her system.

Special Features:

- Solvent Cleaner & Degreaser
- Apply by Brushing, Spraying, Wiping, Soaking
- Especially Effective on Aluminum
- Removes Oils, Tar, Resins, Waxes,
- No Offensive Odor

Recommended For:

- Soak Parts Prior to Automatic Parts Washing
- Use in Vapor Degreasers, Ultrasonic Systems
- Use to Clean Concrete Floors
- Degrease Machinery, Hoods, Etc.



Packaging:

1 Gallon 5 Gallon 15 Gallon
55 Gallon 275 Gallon Bulk