

ArroChem[®] INCORPORATED

SPECIALTY AND INDUSTRIAL CHEMICALS

P.O. Box 5, 201 Westland Farm Road, Mt. Holly, NC 28120
TEL: 704-827-0216 FAX: 704-822-1150
email: contactus@arrochem.com



DECK STRIPPER & CLEANER

General Characteristics:

Appearance:	Clear Colorless Liquid
Chemical Composition:	Caustic Surfactant Blend
Solubility in Water:	Readily Soluble
Lbs. / Gal.	9.89
pH:	12.5 – 13.5
Foaming Nature	Low Foam

Application: *

For best results, apply Arrotech DS&C when the outdoor temperature is between 65°F and 90°F. Dampen the surface desired to be stripped with a light water spray and apply Arrotech DS&C with a brush, roller, pad or sprayer. Do not breathe vapors or mist or allow skin or eye contact. If sprayed, use extra caution and personal protective devices (See MSDS). Let the solution stand for 3-5 minutes, keeping the surface wet with a fine water mist if necessary, then brush with a short, stiff acrylic brush or deck broom. Add more Arrotech DS&C after initial brushing, let stand a second 3-5 minutes, brush again, then rinse well with maximum available household water pressure (or light pressure wash). For paints and solid body stains, full strength product may be required. For heavily worn stains and older oil and latex based sealers and finishes, dilution can be up to four (4) parts water to one (1) part Arrotech DS&C. For general cleaning, a dilution of 20 to 1 is a good starting point.

*As conditions may vary, all dosages and guidelines are merely suggested starting points. It is recommended the user determine the proper operating conditions for their system.



Special Features:

- Extremely Aggressive Caustic Stripper
- Strips Water and Oil Based Paints
- Strips Stains & Varnishes
- Dilute for Heavy Cleaning

For Stripping and Cleaning:

- Wood Decks
- Wood Deck and Patio Furniture
- Wood Siding
- Log Homes
- Wood Planters



Packaging:

1 Gallon 5 Gallon 15 Gallon
55 Gallon 275 Gallon Bulk