



KJ 82 GENERAL PURPOSE CLEANER

General Characteristics:

Appearance:	Translucent Liquid
Chemical Composition:	Alkaline Solution
Wetting:	Rapid
pH, 1% Solution	11.2 ± 0.5
Foaming Nature	Low to Medium

Application: *

Product can be used at full strength to clean dirty, greasy, oily, or ink-soiled surfaces. For pressure wash systems, a dilution of 35 to 50 parts water to one part KJ-82 offers effective cleaning without excessive foaming. For routine cleaning of table tops, sinks, vinyl upholstery, refrigerators, stoves, trucks, buses, aluminum or painted surfaces, shower stalls, stainless steel equipment, flues, conveyors, and mild stains, a dilution of six ounces product per gallon of water provides additional cleaning power. For applications requiring heavy cleaning, a concentrated solution of 16 ounces (one pint) KJ-82 per gallon of water is recommended. As product is water-based, it should not be used at temperatures above 85°C (185°F) or below 5°C (40°F). Always rinse thoroughly after cleaning.

*As conditions may vary, all dosages and guidelines are merely suggested starting points. It is recommended the user determine the proper operating conditions for their system.



Special Features:

- Deep-Cleaning Power
- Excellent Deodorizing Properties
- Non-Hazardous & Non-Flammable
- Concentrated Formula Saves \$\$

Recommended Uses:

- Windows, Sinks, Countertops
- Stainless Steel & Aluminum
- Painted Surfaces & Tile
- Pressure Washing



Packaging:

1 Gallon	5 Gallon	15 Gallon
55 Gallon	275 Gallon	Bulk